



7 Poplar Drive  
 Grangeville, ID. 83530  
 (208) 983-0988 – FAX (208) 983-1390  
 E-Mail: [idsewing@idsewing.com](mailto:idsewing@idsewing.com)  
 Website: [www.idsewing.com](http://www.idsewing.com)

## Square Post Pad Specifications

Features	Benefits
<b>Design</b>	
Velcro® Closure on top of pad.	Allows customer to replace or repair the cover or the foam separate from one another. <b>Decreasing replace, repair, and shipping costs.</b>
Velcro® Flap	Allows for a solid attachment of both edges of the pad creating a strong attachment to the post.
<b>Materials</b>	
<b>Material:</b> 18 oz. <u>coated PVC</u> vinyl	<b>Coated vinyl</b> will not crack and peel as easily as laminated fabrics.
<ul style="list-style-type: none"> <li>• 400 Cycles (Abrasion ASTM D3386)</li> </ul>	<b>High abrasion</b> levels help the material wear longer with extended use.
<ul style="list-style-type: none"> <li>• -40° Cold Crack (ASTM D2136)</li> </ul>	<b>High cold crack</b> gives the product superior resistance to cracking in cold weather and will help the product last longer.
<b>Foam:</b> 1.7lb 90ILD open cell	
<ul style="list-style-type: none"> <li>• 1.7 lb</li> </ul>	Relates to life. The larger number the <b>longer the life</b> with repeated use.
<ul style="list-style-type: none"> <li>• 90 ILD</li> </ul>	Requires 25 lbs of <b>pressure to compress</b> a 12" x 12" x 12" cube to 60% of it's thickness.
<ul style="list-style-type: none"> <li>• <b>Water Resistant</b></li> </ul>	Our foam is specially formulated <b>not to absorb water</b> . It will retain water up to the point it is submerged but will not wick further up, like a sponge.
<b>Thread:</b> #135 21.5 lb black / white	
<ul style="list-style-type: none"> <li>• Extra UVR Protection added</li> </ul>	<b>Resists fading</b> and lasts longer than regular thread in the sun and elements.
<ul style="list-style-type: none"> <li>• Extra Black added</li> </ul>	Resists fading and <b>lasts longer</b> than regular thread in the sun and elements.