



7 Poplar Drive
 Grangeville, ID. 83530
 (208) 983-0988 – FAX (208) 983-1390
 E-Mail: idsewing@idsewing.com
 Website: www.idsewing.com

Square Post Pad Specifications

Features	Benefits
Design	
Velcro® Closure on top of pad.	Allows customer to replace or repair the cover or the foam separate from one another. Decreasing replace, repair, and shipping costs.
Velcro® Flap	Allows for a solid attachment of both edges of the pad creating a strong attachment to the post.
Materials	
Material: 18 oz. <u>coated PVC</u> vinyl	Coated vinyl will not crack and peel as easily as laminated fabrics.
<ul style="list-style-type: none"> • 400 Cycles (Abrasion ASTM D3386) 	High abrasion levels help the material wear longer with extended use.
<ul style="list-style-type: none"> • -40° Cold Crack (ASTM D2136) 	High cold crack gives the product superior resistance to cracking in cold weather and will help the product last longer.
Foam: 1.7lb 90ILD open cell	
<ul style="list-style-type: none"> • 1.7 lb 	Relates to life. The larger number the longer the life with repeated use.
<ul style="list-style-type: none"> • 90 ILD 	Requires 25 lbs of pressure to compress a 12" x 12" x 12" cube to 60% of it's thickness.
<ul style="list-style-type: none"> • Water Resistant 	Our foam is specially formulated not to absorb water . It will retain water up to the point it is submerged but will not wick further up, like a sponge.
Thread: #135 21.5 lb black / white	
<ul style="list-style-type: none"> • Extra UVR Protection added 	Resists fading and lasts longer than regular thread in the sun and elements.
<ul style="list-style-type: none"> • Extra Black added 	Resists fading and lasts longer than regular thread in the sun and elements.