



7 Poplar Drive
 Grangeville, ID. 83530
 (208) 983-0988 – FAX (208) 983-1390
 E-Mail: idsewing@idsewing.com
 Website: www.idsewing.com

Short Track Pad Specifications

Features	Benefits
Design	
Velcro® Closure on back of pad.	Allows customer to replace or repair the cover or the foam separate from one another. Decreasing replace, repair, and shipping costs.
Velcro® Flap	Allows for a solid attachment to the next pad, creating continuous padding around the ice rink.
Handles on Side of Pad	1” Heavy Nylon Web Handles for convenient movement of pads
Mesh Panel on Top of Pad	Air releasing upon impact helping to prevent bounce back
Materials	
Material: 18 oz. <u>coated PVC</u> vinyl	Coated vinyl will not crack and peel as easily as laminated fabrics.
<ul style="list-style-type: none"> • 400 Cycles (Abrasion ASTM D3386) 	High abrasion levels help the material wear longer with extended use.
<ul style="list-style-type: none"> • -40° Cold Crack (ASTM D2136) 	High cold crack gives the product superior resistance to cracking in cold weather and will help the product last longer.
Material: 40 oz. vinyl on front	Heavy duty material withstands contact with skates better than 18 oz. vinyl.
Foam: Progressive Density 1.7lb 90ILD & 1.75lb 60ILD open cell	Softer foam upon impact – denser foam behind for better protection
<ul style="list-style-type: none"> • 1.7 lb & 1.75 	Relates to life. The larger number the longer the life with repeated use.
<ul style="list-style-type: none"> • 90 ILD & 60 ILD 	Requires 25 lbs of pressure to compress a 12” x 12” x 12” cube to 60% of it’s thickness.
<ul style="list-style-type: none"> • Water Resistant 	Our foam is specially formulated not to absorb water . It will retain water up to the point it is submerged but will not wick further up, like a sponge.
Thread: #135 21.5 lb black / white	
<ul style="list-style-type: none"> • Extra UVR Protection added 	Resists fading and lasts longer than regular thread in the sun and elements.