



7 Poplar Drive
 Grangeville, ID. 83530
 (208) 983-0988 – FAX (208) 983-1390
 E-Mail: idsewing@idsewing.com
 Website: www.idsewing.com

Specifications for Tower Pads

| Features | Benefits |
|---|---|
| Design | |
| Velcro® Closure | Allows customer to replace or repair the cover or the foam separate from one another. Decreasing replace, repair, and shipping costs. |
| Custom Padding | All padding is made right here in the USA & can be made any size per your specs |
| Materials | |
| Material: 18 oz. <u>coated PVC</u> vinyl | Coated vinyl will not crack and peel as easily as laminated fabrics. |
| <ul style="list-style-type: none"> • 400 Cycles (Abrasion ASTM D3386) | High abrasion levels help the material wear longer with extended use. |
| <ul style="list-style-type: none"> • -40° Cold Crack (ASTM D2136) | High cold crack gives the product superior resistance to cracking in cold weather and will help the product last longer. |
| Foam: 1.7lb 90ILD open cell | Extra Protection. This project will use 2” thick foam plus an additional 2” piece of foam down the center for a 4” thickness in the middle. |
| <ul style="list-style-type: none"> • 1.7 lb | Relates to life of foam. The larger number the longer the life with repeated use. |
| <ul style="list-style-type: none"> • 90 ILD | Requires 90 lbs of pressure to compress a 12” x 12” x 12” cube to 60% of it’s thickness. |
| <ul style="list-style-type: none"> • Polypropylene Webbing w/ T-Buckles | 1.5” Polypropylene Webbing with 900# tear strength. Black metal 1.5” Buckles -self locking for easy installation and adjustments |
| <ul style="list-style-type: none"> • Water Resistant | Our foam is specially formulated not to absorb water . It will retain water up to the point it is submerged but will not wick further up, like a sponge. |
| Thread: #135 21.5 lb black / white | |
| <ul style="list-style-type: none"> • Extra UVR Protection added | Resists fading and lasts longer than regular thread in the sun and elements. |
| <ul style="list-style-type: none"> • Extra Black added | Resists fading and lasts longer than regular thread in the sun and elements. |