



7 Poplar Drive
 Grangeville, ID. 83530
 (208) 983-0988 – FAX (208) 983-1390
 E-Mail: idsewing@idsewing.com
 Website: www.idsewing.com

Common Top / Weather Cover Specifications

Features	Benefits
Design	
Grommets (#6) around the perimeter of the weather cover every 12"	Allow for universal attachment to the ground over the pads. 12" placement allows for secure attachment and reduces stress.
Sewed seams are double stitched	Last longer and greater strength
Sealed seams on the top of the cover	Makes a water resistant cover
Materials	
Material: 18 oz. coated PVC vinyl	Coated vinyl will not crack and peel as easily as laminated fabrics.
<ul style="list-style-type: none"> • 400 Cycles (Abrasion ASTM D3386) 	High abrasion levels help the material wear longer with extended use.
<ul style="list-style-type: none"> • -40° Cold Crack (ASTM D2136) 	High cold crack gives the product superior resistance to cracking in cold weather and will help the product last longer.
Thread: #135 21.5 lb black / white	
<ul style="list-style-type: none"> • Extra UVR Protection added 	Resists fading and lasts longer than regular thread in the sun and elements.
<ul style="list-style-type: none"> • Extra Black added 	Resists fading and lasts longer than regular thread in the sun and elements.
Webbing: 2" Heavy Duty Polypropylene webbing.	Super heavy for added strength. Higher UV resistance for longer life in the sun and elements.
Grommets: #6 Nickel plated	Resist tarnishing in the weather.
<ul style="list-style-type: none"> • Rolled outside edge 	Prevents grommet from cutting material over time with repeated use.
<ul style="list-style-type: none"> • Spike attachment systems 	Out performs normal solid attachment grommets due to its ability to hold onto the fabric more securely and it creates a nicer looking finish.